

# DEEP PLAST

Quinti®

DEEP PLAST polypropylene shell made of an elegant colors palette. Seven different bases and Essential version with upholstered seat and Soft, make the armchair versatile and able to be integrated in every kind of environment.

1



2



3



4



5



6



7



8



9



- 1 . Armchair with 4 legs frame
- 2 . Armchair with rod frame
- 3 . Armchair with 4 wooden legs
- 4 . Armchair with truss frame
- 5 . Armchair with Light 4 spoke base
- 6 . Armchair with Trend 5 spoke base
- 7 . Armchair with 4 rocking legs frame
- 8 . Armchair with 4 wooden spoke base
9. Benches


- L58/43 P 52/43 H78/44-48  
L58/43 P 52/43 H78/44-48  
L58/43 P 52/43 H78/44-48  
L58/43 P 52/43 H78/44-48  
L70/43 P 70/43 H81/90-47/56-51/60  
L70/43 P 70/43 H81/90-47/56-51/60  
L70/43 P 70/43 H73/42  
L70/43 P 70/43 H79/45  
L120-175-238  
P 61/43 H76/42-46

# DEEP PLAST

Quinti®

## COLOR PALETTES


---



BIANCO  
RAL 9003



CELESTE  
RAL 7001



ANTRACITE  
RAL 7016



NERO CL. I  
RAL 9005



ROSA CIPRIA  
SIKKENS EO.11.67



TORTORA  
RAL 7006



BROWN  
RAL 8017

## STRUCTURE

---

4 metal legs frame diam 16 mm in the finishes:

- Chrome
- Black painted
- Gypsum painted
- Marrone Maserati painted

Rod frame diam 11 mm with ylon feet in the finishes :

- Chrome
- Black painted

4 oak wood painted legs frame

- natural
- tempered

Truss black painted frame

Light 4 spoke Base on castors or feet diam 68 cm and swivel with upliftment

Trend 5 spoke Base on castors diam 68 cm and swivel with upliftment in the finishes:

- Aluminium
- White polypropylene
- Black polypropylene

4 spoke swivel without upliftment Base in painted oak wood:

- natural
- tempered

Black painted truss frame on docking sledges and sleds in natural oak wood.

2/3/4 benches with tripod legs in polished aluminium.

Attached shells with omega attachment and under seat plate on beam 80x40 mm

# DEEP PLAST

**Quinti®**

## PADDING



ESSENTIAL



SOFT SEAT



SOFT

Deep is available in three versions:

- ESSENTIAL \_ polypropylene shell without padding
- SEDILE SOFT \_ shell with padded seat in polyurethane rubber density 40 with supportive wooden structure.
- SOFT \_ entirely and internally padded shell with cold foam polyurethane.

Both Soft versions are available with MINISTERIAL CERTIFICATION 1 IM



**CREPE'**

350 gr/mtl  
100% Poliestere Classe 1 ,EN1021/1-2  
50.000 +/- 10% cicli Maltindale

**BIO-EXPO****CATEGORY 2**

300 gr/mt2  
100% Propitex FR batteriosattico  
Classe 1UNI EN ISO 354:2003  
100.000 +/- 10% cicli Maltindale

**EXTREME****CATEGORY 2**

350 gr/mtl  
100% Xtreme FR  
Classe , EN 1021-1/2  
100.000 +/- 10% cicli Maltindale

**LASER****CATEGORY 2**

560 gr/mtl  
100% Poliestere FR  
Classe 1  
80.000+/- 10% cicli Maltindale

**ECOPELLE****CATEGORY 2**

630 gr/mt2  
83% PVC, 17% Syntetic  
ISO 379-DIN75200-CSERF4/83 10%  
cicli Maltindale

**ERA****CATEGORY 3**

448 gr/mtl  
100% Trevira CS  
Classe 1UNI EN ISO 354:2003  
100.000 +/- 10% cicli Maltindale

**LASER PLUS****CATEGORY 3**

630 gr/mtl  
100% Poliestere FR Trevira  
Classe1 , 4.000 +/- cicli Maltindale

**ECOPELLE SOUL****CATEGORY 3**

760 gr/mt2  
Superficie 100% POLIURETANO,  
Base Poliestere 85%,17% Cotone  
E>100.000 EN ISO 5470-2 /1

**MELANGE****CATEGORY 3**

390 g/lin.m  
100% Trevira CS  
Classe 1  
80.000 +/- 10% cicli Maltindale

**JET****CATEGORY 3**

365+/- 5% g/lin.m  
100% Poliestere FR  
Classe 1  
80.000+/- 10% cicli Maltindale

**ECOPELLE SISTEMA PRO****CATEGORY 3**

710 gr/mt2  
Superficie 93% PVC  
Base Poliestere 28%  
CLASSE1  
100.000 CICLI

**LANA****CATEGORY 5**

500 gr/mt2  
75% Lana, 25% poliammide  
Classe 1  
100.000 cicli Maltindale

**PELLE****CATEGORY 5/6**

620 g/lin.m  
100% Pelle bovina  
Classe 1, EN 1021-1/2

**PIED POULE****CATEGORY 6**

550 g/lin.m  
66% cotone, 34% Poliestere  
35.000 % cicli Maltindale

**EUROPOST 2****CATEGORY 6**

710 g/lin.m  
63% PU, 16% CO, 21% PL  
Ini1975 CLASSE1emme,UNI9175/FA  
50.000% cicli Maltindale

**PREMIUM /ELEGANCE****CATEGORY 7**

100% Pelle bovina Primo fiore  
Spessore 1,2/1,4 mm  
EN1021-1/2

**MERIT****CATEGORY**

500g/lin.m  
76% Poliestere Recycled  
24% Poliestere  
EN 1021-1/2  
85.000 % cicli Maltindale

**REMIX****CATEGORY 7**

415 g/lin.m  
90% New wool worsted, 10% Nylon  
Classe 1, EN 1021-1/2  
100.000 % cicli Maltindale

**STEELCUT TRIO****CATEGORY 7**

770 g/lin.m  
90% New wool worsted, 10% Nylon  
Classe 1, EN 1021-1/2  
100.000 % cicli Maltindale

**VELLUTO DECONTRACTE'****CATEGORY 7**

590 g/lin.m  
19% CO, 61% PC,10% PL, 10%VI  
40.000 % cicli Maltindale

**VELLUTO****CATEGORY 8**

600 g/lin.m  
100.000 % PL Flame retardant

**PELLE SOFT****CATEGORY 8**

100% Pelle bovina SPESSORE1,8-2 mm  
Primo fiore CONCIA ALL'ANILINA  
EN1021-1/2

**RETE GABRIEL**

510 gr. gr/mtl  
100% Poliestere / Polyester  
BS EN 1021-1:2014  
70.000 cicli / rubs

## USAGE AND CARE

For a proper maintenance of the products and to maintain unchanged the characteristics of the materials, we recommend to follow some very simple care instructions.

### FABRICS

Cleaning: check the dedicated selection written on the color Swatch card. Usage: it is recommended to pay attention to the fabrics as they can be easily cut or ripped.

### LEATHERS

Cleaning: clean with a white wet cloth with water. We recommend to use high quality products for the cleaning of the leather and to follow carefully the instructions of the manufacturer. In doubt, try out the product on a hidden part and wait at least 24 hours for the occurrence of any problems. Usage: remember that the leather is a delicate material therefore it is recommended to pay particular attention while using.

### WOODS

Cleaning: clean with a soft and wet cloth with warm water. We always recommend to dry immediately after the cleaning process. All liquids or other residue must be removed in order to avoid the absorption. Usage: wooden surfaces, being a natural material, could be affected by an alteration of the color shade during time and use. We also remind that wooden surfaces cannot bear with high temperatures if placed directly on the wooden top.

### METALS

Cleaning: both steel or aluminium surfaces, and painted ones, must be cleaned with a soft and wet cloth with hot water. For the most persistent stains, a small amount of liquid soap diluted in water may be used. We always recommend to dry immediately with a soft cloth or a leather one after the cleaning process. Never using cleaning products for steel, chlorine, bleach or other strong detergents. It is not recommended to use abrasive creams, score pads and abrasive sponges that can scratch the metal surfaces. Usage: pay attention to the stains of food such as coffee, coke, fruit juices that can leave indelible marks on the surface.

### WARRANTY

QUINTI guarantees the products will maintain their properties for 6 years from delivery, except normal usury and provided that they will be used according to the guidelines given. QUINTI will replace, free of charge, any product found non-compliant with this warranty, without incurring any other liability of sort. Components, external accessories or materials supplied by the buyer and applied to the products in order to customize them will not be supported by the guarantee. For an optimal maintenance of the products and to keep unchanged the characteristics of the materials with which they are made, some simple attentions are necessary.