

NELSON BUBBLE PENDANT COLLECTION

PRODUCT FACT SHEET



NELSON BUBBLE PENDANT COLLECTION

DESIGN FOR HERMAN MILLER, AVAILABLE FROM HAY, 1947

Designed by pioneering American designer George Nelson in 1947, and first produced in 1952, the Bubble Lamp signaled a revolution in the Modernist lighting industry. Available in an assortment of organic sizes and shapes, these elegant orbs were inspired by a set of silk-covered Swedish pendant lamps Nelson wanted for his office, but found to be too expensive. Employing the resourcefulness that characterized his working process, he decided to use a self-webbing plastic spray developed by the U.S. military, and applied it over a lightweight, rounded-steel frame to produce these soft, glowing fixtures.

HIGHLIGHTS

- Part of a progressive and technologically advanced lighting collection.
- A family of refined pendants.
- CE approved.
- Designed for use with a replaceable standard retro fit LED dimmable bulb.
- Suitable for both private and office environments.

MATERIALS

SHADE

Webbing polymer.

FRAME TOP & BOTTOM RING

Coated and brushed metal and nickel.

CORD

White PVC insulation.

All Bubble Lamp models have a steel-wire skeleton on the interior which is spray coated with the translucent plastic polymer resulting in a lamp that is both opaque and transparent as it glows.


COLOUR & FINISH

Please note that the colour codes are indicative.




OFF WHITE


DIMENSIONS




BALL | SMALL
DIAMETER 32,5 CM | 12.80"
HEIGHT 30,5 CM | 12"




BALL | MEDIUM
DIAMETER 48,5 CM | 19.09"
HEIGHT 39,5 CM | 15.55"




BALL | LARGE
DIAMETER 68 CM | 26.77"
HEIGHT 59,5 CM | 23.43"




SAUCER | SMALL
DIAMETER 44,5 CM | 17.52"
HEIGHT 18 CM | 7.10"



SAUCER | MEDIUM
DIAMETER 63,5 CM | 25"
HEIGHT 25,5 CM | 10.04"




SAUCER | LARGE
DIAMETER 89 CM | 35.04"
HEIGHT 35,5 CM | 13.98"




SAUCER | X-LARGE
DIAMETER 127 CM | 50"
HEIGHT 56 CM | 22.05"


- NELSON BUBBLE PENDANT COLLECTION -




CIGAR | SMALL
DIAMETER 26,5 CM | 10.43"
HEIGHT 35,5 CM | 13.98"




CIGAR | MEDIUM
DIAMETER 33 CM | 13"
HEIGHT 53 CM | 20.87"




CIGAR | LARGE
DIAMETER 38 CM | 14.96"
HEIGHT 84 CM | 33.07"




CIGAR | X-LARGE
DIAMETER 47,5 CM | 18.70"
HEIGHT 127 CM | 50"




SAUCER CRISSCROSS | SMALL
DIAMETER 44,5 CM | 17.52"
HEIGHT 15 CM | 5.90"




SAUCER CRISSCROSS | MEDIUM
DIAMETER 63,5 CM | 25"
HEIGHT 24 CM | 9.45"




BALL CRISSCROSS | SMALL
DIAMETER 32,5 CM | 12.8"
HEIGHT 30,5 CM | 12"




BALL CRISSCROSS | MEDIUM
DIAMETER 48,5 CM | 19.1"
HEIGHT 39,5 CM | 15.5"




CIGAR CRISSCROSS | SMALL
DIAMETER 26,5 CM | 10.43"
HEIGHT 35,5 CM | 13.98"




CIGAR CRISSCROSS | MEDIUM
DIAMETER 33 CM | 13"
HEIGHT 53,5 CM | 21.06"




PEAR | SMALL
DIAMETER 33 CM | 13"
HEIGHT 32 CM | 12.60"




PEAR | MEDIUM
DIAMETER 43 CM | 16.93"
HEIGHT 48 CM | 18.90"




PEAR CRISSCROSS | SMALL
DIAMETER 33 CM | 13"
HEIGHT 32 CM | 12.60"




PEAR CRISSCROSS | MEDIUM
DIAMETER 43 CM | 16.93"
HEIGHT 48,5 CM | 19.09"




APPLE | MEDIUM
DIAMETER 53,5 CM | 21.06"
HEIGHT 37 CM | 14.60"



LANTERN | SMALL
DIAMETER 28 CM | 11.02"
HEIGHT 26,5 CM | 10.43"



PROPELLER | MEDIUM
DIAMETER 28 CM | 11.02"
HEIGHT 26,5 CM | 10.43"



BELL | X-LARGE
DIAMETER 106,5 CM | 41.93"
HEIGHT 73,5 CM | 28.94"

SMALL TECHNICAL SPECIFICATIONS

RECOMMENDED LIGHT SOURCE*	POWER (WATTS)	DIMMABLE	POWER SUPPLY	CORD LENGTH	SWITCH
LED E27 (A15)	5-8W	Yes**	220-240V AC at 50/60Hz	183 cm	No

*Bulb not included

**If used in conjunction with a wall mounted dimmer and suitable LED bulb. Bulb not included. Hardwiring required.

TEST SPECIFICATIONS*

FLUX (LUMENS)	CCT (KELVIN) & CRI (1-100)
500-800m	The levels will vary depending on the type of bulb used in the lamp.

*Photometrics and the specification shown is taken using the recommended LED bulbs fitted in the production luminaire.

MEDIUM TECHNICAL SPECIFICATIONS

RECOMMENDED LIGHT SOURCE*	POWER (WATTS)	DIMMABLE	POWER SUPPLY	CORD LENGTH	SWITCH
LED E27 (A19)	10-13W	Yes**	220-240V AC at 50/60Hz	183 cm	No

*Bulb not included

**If used in conjunction with a wall mounted dimmer and suitable LED bulb. Bulb not included. Hardwiring required.

TEST SPECIFICATIONS*

FLUX (LUMENS)	CCT (KELVIN) & CRI (1-100)
1000-1500m	The levels will vary depending on the type of bulb used in the lamp.

*Photometrics and the specification shown is taken using the recommended LED bulbs fitted in the production luminaire.

LARGE TECHNICAL SPECIFICATIONS

RECOMMENDED LIGHT SOURCE*	POWER (WATTS)	DIMMABLE	POWER SUPPLY	CORD LENGTH	SWITCH
LED E27 (A21 or G30)	10-13W	Yes**	220-240V AC at 50/60Hz	183 cm	No

*Bulb not included

**If used in conjunction with a wall mounted dimmer and suitable LED bulb. Bulb not included. Hardwiring required.

TEST SPECIFICATIONS*

FLUX (LUMENS)	CCT (KELVIN) & CRI (1-100)
1000-1500m	The levels will vary depending on the type of bulb used in the lamp.

*Photometrics and the specification shown is taken using the recommended LED bulbs fitted in the production luminaire.

X-LARGE TECHNICAL SPECIFICATIONS

RECOMMENDED LIGHT SOURCE*	POWER (WATTS)	DIMMABLE	POWER SUPPLY	CORD LENGTH	SWITCH
LED E27 (A21 or G30)	10-13W	Yes**	220-240V AC at 50/60Hz	274 cm	No

*Bulb not included

**If used in conjunction with a wall mounted dimmer and suitable LED bulb. Bulb not included. Hardwiring required.

TEST SPECIFICATIONS*

FLUX (LUMENS)	CCT (KELVIN) & CRI (1-100)
1000-1500m	The levels will vary depending on the type of bulb used in the lamp.

*Photometrics and the specification shown is taken using the recommended LED bulbs fitted in the production luminaire.

CERTIFICATES

CE APPROVED

This product has been assessed and complies with the essential requirements of the relevant European directives.

LED  IP20  

Tested according to the following european EN IEC standards which relate specifically to electrical lighting products including

- EN 60598-2-4:1997 (portable luminaires)
- EN 60598-1:2015 (general requirements)

COUNTRY OF ORIGIN

USA

DOWNLOADS

Packshots and lifestyle photos, 2D / 3D files, care and maintenance, instructions, test certificates, product fact sheets, and product presentations are available in our Image Bank at hay.com.

LINK TO DIGITAL LIBRARY